

CERTIFICATE OF ANALYSIS

CEC EXPERIMENTATION FUEL DF-92-02 (for HFRR Test)

HIGH LUBRICITY REFERENCE FUEL

Batch-No.: OC13513A14 **Tank:** Drum **GMID:** 220279 **Date of Analysis:** 13.03.2000

Feature	Units	Result	Limits		Method
			Minimum	Maximum	
Density at 15°C	kg/m ³	839,7	830	850	ISO 12185
Distillation					ISO 3405
I.B.P.	°C	185,2		Report	
- 10 % v/v	°C	214,7		Report	
- 50 % v/v	°C	267,9		Report	
- 90 % v/v	°C	334,4		Report	
F.B.P.	°C	365		370	
Flash Point	°C	71	61		ISO 2719
Aromatics	% v/v	27,2		Report	IP 391
Viscosity 40 °C	mm ² /s	2,734		Report	EN ISO 3104
Sulfur Content	% m/m	0,277	0,25	0,3	EN 24260
Conradson Carbon	% m/m	<0,03		0,2	EN ISO 10370
Residue (10 % DR)					
Ash Content (tested by subcontractor)	% m/m	0,005		0,01	ISO 6245
Water Content	% m/m	0,006		0,05	ISO 12937
Oxidation Stability	mg/100ml	0,3		2,5	ISO 12205

Parameters according to CEC-F-06-A-96 results of Round Robin Test:

HCF	12	µm/kPa
WS1.4	420 +/- 36	µm

The lubricity reference fuel has to be approved in a round robin test of the CEC Working Group SG-F-006. The value and the limits for the wear scar and the humidity correction factor are estimated in the round robin.

Haltermann Products, Werk Hamburg,
 Zweigniederlassung der DOW Olefinverbund GmbH
 - Labor - Quality Manager
 Christine Behrens



This Certificate of Analysis applies to: **Date of Printing** **26.02.2009**

Order No.: <u>07020330</u>	Customer Order No. <u>B280047</u>
Date: <u>24.04.2009</u>	Signature: <u>K. Jacobi</u>

DIN EN ISO/IEC 17025

 Registriernummer: DAC-PL-416-05-40

Haltermann Products,
 Zweigniederlassung der Dow Olefinverbund GmbH
 Schlegendeich 17, D-21107 Hamburg
 T +49-(0)40-75 104-0
 F +49-(0)40-75 104-113